

iM-100 Series

SPECIFICATIONS

intelligence Measurement Station

| Model | iM-101 | iM-102 | iM-103 | iM-105 |
|---|--|---|--------|--------|
| Telescope | 30x / 2.5" | | | |
| Magnification / Resolving power | Length : 171mm (6.7in.), Objective aperture : 45mm (1.8in.) (48mm (1.9in.) for EDM), Image: Erect, Field of view: 1°30' (26m/1,000m), Minimum focus: 1.3m (4.3ft.) Reticle illumination: 5 brightness levels | | | |
| Others | | | | |
| Angle measurement | | | | |
| Minimum Display | 0.5"/1" (0.0001 / 0.0002gon, 0.002 / 0.005mil) | 1"/5" (0.0002 / 0.001gon, 0.005 / 0.02mil) | | |
| Accuracy (ISO 17123-3:2001) | 1" | 2" | 3" | 5" |
| Dual-axis compensator | Dual-axis liquid tilt sensor, working range: ±6' | | | |
| Collimation compensation | On/Off (selectable) | | | |
| Distance measurement | | | | |
| Laser output ¹ | Reflectorless mode : Class 3R / Prism/sheet mode : Class 1 | | | |
| Measuring range | 0.3 to 800m (2,620ft.) / Under good conditions ⁴ : 1,000m (3,280ft.) | | | |
| (under average conditions ²) | Reflectorless ³ | RS90N-K: 1.3 to 500m (4.3 to 1,640ft.), RS50N-K: 1.3 to 300m (4.3 to 980ft.), RS10N-K: 1.3 to 100m (4.3 to 320ft.) | | |
| | Reflective sheet ^{5,6} | 1.3 to 500m (4.3 to 1,640ft.) | | |
| | Mini prism | 1.3 to 5,000m (4.3 to 16,400ft.) / Under good conditions ⁴ : 6,000m (19,680ft.) | | |
| | One prism | Fine / Rapid : 0.0001m (0.001ft. / 1/16 in.) / 0.001m (0.005ft. / 1/8 in.) (selectable) Tracking / Road : 0.001m (0.005ft. / 1/8 in.) / 0.01m (0.02ft. / 1/2 in.) (selectable) | | |
| Minimum Display | | | | |
| Accuracy ^{7,8} | Reflectorless ³ | (2 + 2ppm x D) mm ⁸ | | |
| (ISO 17123-4:2001) | Reflective sheet ^{5,6} | (2 + 2ppm x D) mm | | |
| (D=measuring distance in mm) | Prism ⁷ | (1.5 + 2ppm x D) mm | | |
| Measuring time ^{4,9} | Fine | 0.9s (initial 1.5s) | | |
| | Rapid | 0.6s (initial 1.3s) | | |
| | Tracking | 0.4s (initial 1.3s) | | |
| OS, Interface and Data management | | | | |
| Operating system | Linux | | | |
| Display / Keyboard | Graphic LCD, 192 x 80 dots, backlight, contrast adjustment / Alphanumeric keyboard / 28 keys with backlight | | | |
| Control panel location | On both faces | | | |
| Trigger key | Yes (right side) | | | |
| Data storage | Internal memory | Approx. 50,000 points | | |
| | Plug-in memory device | USB flash memory (max. 32GB) | | |
| Interface | Serial RS-232C, USB2.0 (Type A for USB flash memory) | | | |
| | Bluetooth modem (option) ¹⁰ | Bluetooth Class 1.5, Operating range: up to 10m ¹¹ | | |
| General | | | | |
| Guide light ¹² | Green LED (524nm) and Red LED (626nm), Operating range: 1.3 to 150m (4.3 to 490ft.) | | | |
| Laser-pointer ¹² | Coaxial red laser using EDM beam | | | |
| Levels | Graphic | 6' (Inner Circle) | | |
| | Circular level (on tribrach) | 10' / 2mm | | |
| Plummet | Optical | Magnification: 3x, Minimum focus: 0.5m (19.7in.) from tribrach bottom | | |
| | Laser (option) | Red laser diode (635nm±10nm), Beam accuracy: <=1.0mm@1.3m, Class 2 laser product | | |
| Dust and water protection / Operating temperature | IP66 (IEC 60529:2001) / -20 to +60°C (-4 to +140°F) | | | |
| Size with handle | 183(W)x 181(D)x 348(H)mm | | | |
| Instrument height | 192.5mm from tribrach mounting surface | | | |
| Weight with battery & tribrach | Approx. 5.3kg (11.7lb) | | | |
| Power supply | | | | |
| Battery | Li-ion rechargeable battery BDC70 | | | |
| Operating time (20°C) ¹³ | BDC70: Approx. 28hours ¹⁴ | | | |
| Application program | | | | |
| On board | <ul style="list-style-type: none"> • REM Measurement • 3D Coordinate Measurement • Resection • Stake Out • Topography Observation • Offset Measurement • Missing Line Measurement • Intersection • Surface Area Calculation • Route Surveying • Point to Line | | | |

*1 IEC60825-1:Ed.2.0:2007/ FDA CDRH 21 CFR Part 1040.10 and 11 *2 Average conditions: Slight haze, visibility about 20km (12 miles), sunny periods, weak scintillation. *3 With Kodak Gray Card White Side (90% reflective). When brightness on measured surface is 30,000 lx. or less. Reflectorless range/accuracy may vary according to measuring objects, observation situations and environmental conditions. *4 Good conditions: No haze, visibility about 40km (25miles), overcast, no scintillation. *5 When the measuring beam's incidence angle is within 30° in relation to the reflective sheet target. *6 Measuring range in temperatures of 50 to 60°C (122 to 140°F): RS90N-K: 1.3 to 300m (4.3 to 980ft.), RS50N-K: 1.3 to 180m (4.3 to 590ft.), RS10N-K: 1.3 to 60m (4.3 to 190ft.) *7 Face the prism toward the instrument during the measurement with the distance at 10 m or less. *8 Measuring range: 0.3 to 200m *9 Fastest time under good conditions, no compensation, EDM ALC at appropriate setting, slope distance. *10 Usage approval of Bluetooth wireless technology varies according to country. Please consult your local office or representative in advance. *11 No obstacles, few vehicles or sources of radio emissions/interference in the near vicinity of the instrument, no rain. *12 The laser-pointer and the guide light do not work simultaneously. *13 Figures will change depending on the operating environment including temperatures and observation conditions. *14 In use of ECO mode. Fine single measurement every 30sec.

Standard Package Components

- Main unit • Battery (BDC70) • Battery charger (CDC68A) • Power Cable • Lens cap • Lens hood • Tool pouch • Precision Screwdriver • Lens brush
- Hexagonal wrench x2 • Cleaning cloth • Quick Manual • CD-ROM (Operation manual) • Laser caution sign-board • Carrying case • Carrying strap

SOKKIA

Topcon Positioning Middle East and Africa FZE
P.O.Box 371028, LIU J-11, Dubai Airport Free Zone, Dubai, UAE
Phone : (+971)4-299-0203 Fax : (+971)4-299-0403
E-mail : marketing@topcongulf.com
Website : www.topconpositioningmea.com

Your local Authorized Dealer is:

- Specifications may vary by region and are subject to change without notice.
- Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Topcon is under license.
- Other trademarks and trade names are those of their respective owners.

SOKKIA

iM-100 Series

intelligence Measurement Station

Evolving Entry-Level Total Station

- Construction and Survey Application Software On Board
- Best-in-Class Measuring Distance Feature
- Reliable Large Volume Internal Memory
- Long-Hour Battery Operation
- Strong Environmental Specification Against Tough Sites



Construction and Survey Application Software On Board Reliable All-Round Total Station



Construction

Cross-Sectional Survey

By using the MLM (Missing Line Measurement) program, the height difference between points can be calculated. Also, you can save time on reflectorless mode to measure a number of points of variation in a large area.

Stake Out

The Guide Light function will navigate the prism operator to move to the stake out line quickly so that stake out operation can be done effectively.

Elevation Stake

Staking out with 3D coordinates, eliminates the need to set up TS on the straight line for all elevation stakes.

Boundary and Cadastral Survey

By using the Area function, you can calculate the area easily. Also, you can determine the center point of the column such as electric pole, which cannot be directly measured, by using offset calculation.

Coordinate Measurement

With coordinate measurement, you can manage 3D coordinate data so that various calculations such as Road, Layout and more can be determined. 3D coordinate data management can improve the productivity drastically.

Topographic Survey

The trigger key, or measuring distance key, helps you perform topography quickly while continuously viewing through the telescope. Also, the long distance measuring range reduces the number of the instrument changes for more efficient working time.

Survey

Improve Topography and Stake Out, with features to achieve faster and more efficient workflows

Newly Designed High-End Class EDM

Especially effective in surveying control points that require high-accuracy, and in cross sectional surveying in large areas with reflectorless measurement mode.

All Features are at Top Class

| | Accuracy | Measuring Range |
|---------------|------------|-----------------|
| Prism-Mode | 1.5mm+2ppm | 6,000m* |
| Reflectorless | 2.0mm+2ppm | 1,000m* |

* Good atmospheric condition

Distance Measurement Accuracy (Prism Mode)

iM Accuracy **1.5mm+2ppm**
Previous Model 2.0mm+2ppm

Measuring Range(Reflectorless Mode)

iM Distance **1,000m**
Previous Model 500m

Reliable Large Volume Memory

Internal memory has 50,000 points to record. USB memory can be used up to 32GB.

IoT Support System - Connect the Site and the Office

TSshield IoT Support System

- Remotely update the firmware via the internet
- Improves asset management by checking TS operating time
- Remote Lock secures the instrument from theft.
- Monitor TS health status to enable quick reaction against any functionality issues

*This service may not be available in some areas.

IoT

Superior Basic Feature will Expand Your Application

Strong Environmental Spec

The IP66 rating ensures durability for most any rough job site temperatures and conditions.

Long Hours Operation

One battery lasts up to 28 hours, or about four days of normal operation time.

Bright Illumination Key for Nighttime Work

Key buttons are illuminated to minimize mistakes.

Reliable Large Volume Memory

Internal memory has 50,000 points to record. USB memory can be used up to 32GB.

Japan Quality Products



We perform the tough environmental tests to ensure long-term operation even under the rough site environments.

iM Series total stations are thoroughly inspected with dust-proof and water-proof test chambers.

In addition, the various tests against vibration, drop, temperature, and humidity were successfully passed to achieve the best environmental spec. Also, the measuring distance accuracy test on base line and the instrument leveling and angle accuracy test and adjustment by collimator system ensure your satisfaction on iM Series product quality.

